

DYNAMIC™ FLOOR ETCH

PRODUCT DESCRIPTION:

Dynamic Floor Etch is a wash on-wash off liquid that microscopically roughens ceramic, quarry, porcelain, concrete and other stone surfaces to create a long lasting slip resistant surface.

<u>PRODUCT FEATURES</u>	<u>USER BENEFITS</u>
<ul style="list-style-type: none">• Increases Coefficient of Friction• Easy to Use• Creates Less Hazardous Floor Surfaces	<ul style="list-style-type: none">• Reduces Potential for Slip and Fall Accidents• Apply by brush, sprayer, foamer or automated equipment• Reduces Worker's Compensation Costs• Reduces Lost Work Hours• Reduces Medical Costs• Increases Productivity

DIRECTIONS FOR USE:

1. Work in a small area that you can control. Test floor to determine optimum contact time - one (1) to fifteen (15) minutes. Apply generous amount of Floor Etch to surface with mop, applicator, or sprayer. Let stand for contact time determined above.
2. Scrub with deck brush or automated floor scrubbing equipment.
3. Rinse thoroughly with clean water.
4. Squeegee standing water to floor drains or mop area with clean water.

DYNAMIC

RESEARCH COMPANY, INC.

FOR ADDITIONAL INFORMATION

DYNAMIC RESEARCH COMPANY, INC.

Safety Products Division
4800 SW Meadows Road - Suite 300
Lake Oswego, Oregon 97035
503-699-1335 FAX 503-699-1094
Order Desk: 800-876-2232
URL <http://www.saf-t-step.com>